Yuasa Technisches Datenblatt

YBX3100 - YBX 3000 SMF Batteries

Leistung

Nennspannung	12 V
Kapazität (20 Stunden)	71 Ah
Bewertet mit CCA	680 A



Maße (±2 mm)

Länge	278 mm
Breite	175 mm
Höhe	175 mm

Maße und Gewichte

Gewicht	17.1 kg

Gehäuseeigenschaften

Art des Gehäuses	LB3 DIN
Terminal-Typ	T1
Bodenleiste	B13/B14
Ladezustandsanzeige	Ja
Griffe	Ja
Pol-Entlüftung	Ja
Deckel-Typ	SMF

Technologie

Flammensperre	Ja
Technologie	Ca/Ca
Typ des Separators	PE
VDA-Rollover-Test	Ja
Empfohlener Laderate (A)	5 A
Leistungskennzeichnung	W3-C2-V2-E1

Gehäuseeigenschaften

T1

Standard DIN Post



Zellenanordnung



Batteriehalter



Yuasa Technical Data Sheet

YBX3100 - YBX 3000 SMF Batteries

Performance

Nominal Voltage	12 V
Capacity (20hr)	71 Ah
Rated CCA	680 A



Dimensions (±2mm)

Length	278 mm
Width	175 mm
Height	175 mm

Weights & Measures

Weight	17.1 kg

Container Features

Case Type	LB3 DIN
Terminal Type	T1
Hold-down	B13/B14
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF

Technology

Flame Arrestor	✔
Technology	Ca/Ca
Separator Type	PE
VDA Roll Over Test	✔
Recommended Charge Rate (A)	5 A
Performance Marking	W3-C2-V2-E1

Terminal Type

T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



YUASA
by GS YUASA

www.yuasa.com